


## NUTR2562 [🔗](#)

### 支撑型滚轮

Yoke type track rollers NUTR...-A, double row cylindrical roller bearings with particularly thick-walled outer ring, full complement cylindrical roller set and an inner ring, the outer ring is guided axially by the rolling elements, labyrinth seals on both sides

## 技术信息



### 您当前的产品型号

|       |     |                               |
|-------|-----|-------------------------------|
| 密封    | 2LB | Labyrinth seals on both sides |
| 修形外圈  | IOP | Optimized INA-profile         |
| 再润滑特性 | IR  | Via inner ring                |

### 主要尺寸和性能数据

|                    |             |             |
|--------------------|-------------|-------------|
| d                  | 25 mm       | 内径          |
| D                  | 62 mm       | 外径          |
| B                  | 25 mm       | 内圈宽度        |
| C <sub>rw</sub>    | 35,500 N    | 基本额定动载荷, 径向 |
| C <sub>0rw</sub>   | 54,000 N    | 基本额定静载荷, 径向 |
| C <sub>urw</sub>   | 7,000 N     | 疲劳极限载荷, 径向  |
| n <sub>DG</sub>    | 4,200 1/min | 脂润滑转速       |
| F <sub>0rper</sub> | 54,000 N    | 容许径向静载荷     |
| F <sub>rper</sub>  | 54,000 N    | 容许径向动载荷外圈   |
| ≈m                 | 0.445 kg    | 重量          |

### 尺寸

|                    |        |           |
|--------------------|--------|-----------|
| C                  | 24 mm  | 外圈宽度      |
| d <sub>2</sub>     | 31 mm  | 止推垫圈的止推直径 |
| r <sub>min</sub>   | 1 mm   | 最小倒角尺寸    |
| r <sub>1 min</sub> | 0.5 mm | 最小倒角尺寸    |